

# VTH1550CHM

IP Indoor Monitor



## Features

- 7" TFT Capacitive touch screen
- IPC surveillance
- Alarm integration
- Micro SD card optional, max 32GB
- Record & Snapshot(SD card needed)



## Technical Specification

Model	VTH1550CHM
-------	------------

### System

Main Processor	Embedded Micro Processor
----------------	--------------------------

Operation System	Embedded LINUX OS
------------------	-------------------

### Video

Video Compression	H.264
-------------------	-------

### Audio

Audio Compression	G.711
-------------------	-------

Audio Input	All-direction Microphone
-------------	--------------------------

Audio Output	Built-in Loudspeaker
--------------	----------------------

Bidirectional Talk	Support Dual-way Bidirectional talk
--------------------	-------------------------------------

### Display

LCD Screen	7" 800x480, Capacitive
------------	------------------------

### Operation Mode

Input	Touch buttons
-------	---------------

### Interface

Alarm In	8
----------	---

RS485	1
-------	---

### Network

Ethernet	10M/100Mbps Self-adaptive
----------	---------------------------


Network Protocol	TCP/IP
------------------	--------

### General


Memory Slot	Micro SD, Max 32GB
-------------	--------------------

Installation	Flush
Power	DC 12V/ supply directly by VTNS1060A
Power Consumption	Standby ≤1.5W, Work ≤7W
Working Temperature	-10°C~+55°C
Relative Humidity	10%~90%RH
Dimensions	200.5mm×136.5mm×22.0mm
Weight	1.0Kg

Dimensions



View Area



Application

